

کولر کانالی، خرطومی BSCH

BSCH Canneled Cooler

Canneled Cooler  
Digital Temperature  
Industrial Construction  
High Unit Efficiency  
Easy Maintenance



DATA	BSCH 1000	BSCH 2000	BSCH 3000	BSCH 4000	BSCH 7000
Type	channeled				
Cooling cap I35	1000 Watt	1700 Watt	2700 Watt	4000 Watt	7000 Watt
Type of refrigerant	R134a			R22	R22
Amount of refrigerant	650 gr	750 gr	800 gr	1100 gr	1950 gr
Rated frequency	50/60 Hz				
Standard power supply	198 V-252 V				
Power absorbed L35 L35	690 W	890 W	1200 W	1870 W	2150 W
Compressor	DANFOSS			KULTHORN	KULTHORN
Ambient temp	+15°C ...+55°C				
internal fan type	Forward				
internal circuit	300(m3/h)	300(m3/h)	620(m3/h)	2×620(m3/h)	2×660(m3/h)
External fan type	Axial				
External circuit	780(m3/h)	780(m3/h)	960(m3/h)	2030(m3/h)	2×2030(m3/h)
Control range	+30°...+45°C				
Factory setting	+30°C				
Condensation discharge	RAL 7047				
Weight	40 kg	55 kg	63 kg	76 kg	108 kg
H×W×D /mm	850×400×275	1000×410×315	1100×460×315	1400×460×380	1400×650×650
IP	54				

Technical Specifications